

## GTEK™ COMPOUND TECHNICAL SHEET

GTEK™ Stud Adhesive is a specially formulated water-based acrylic adhesive used for fixing plasterboard to timber and metal studs for wall and ceiling linings. Stud adhesive must be used in conjunction with nails or screws, it does not constitute a fixing system on its own.

### GTEK™ Stud Adhesive

- ▶ Pre mixed and ready to use
- ▶ Fast grab, no slump
- ▶ High bond strength
- ▶ Can be used on treated and untreated timber
- ▶ Available in 1.25kg and 5.2kg buckets



## GTEK™ COMPOUND TECHNICAL SHEET

### Preparation

Do not store outside. Ensure all surfaces are free of dust, grease, oil or foreign matter.

### Application

Stud Adhesive should not be applied to wet or green timber. Apply Stud Adhesive in dollops 25mm in diameter and 15mm high.

On walls, dollops are to be applied at 300mm maximum centres and a minimum of 200mm from the edges of the sheet.

On ceilings, dollops are to be applied at 230mm maximum centres and a minimum of 200mm from the edges of the sheet.

Plasterboard linings should be pressed firmly against Stud Adhesive. Do not apply Stud Adhesive within 200mm of nailing or screwing points. Do not apply adhesive at window and door openings or at butt joints.

Fasten plasterboard in accordance with manufacturer's instructions.

**Note** / Stud Adhesive is not to be used as part of a fire rated system (FRL). Mechanical fasteners (screws and nails) only to be used in fire rated systems.

To maximise shelf life, protect from extreme heat and cold and keep lid tightly closed when not in use.

